

BAN DALAM TRAKTOR	
SIZE	VALVE
250/8.15-15	TR177A
8-16	TR13
8-16	TR75A
8-18	TR15
12.5/80-18	TR218A
14.00-20	TR78A
16.0/70-20	TR75A
8.3/8-24	TR218A
9.3/9-24	TR218A
12.4-24	TR218A
12.4/13.6-24	TR218A
13.00/14.00R24	TR78
13.00/14.00R24	TR78 HD
13.00/14.00R24	TR179
14.00-24	TR179A
14.9-24	TR218A
16.9-24	TR218A
13.6/14.9R-26	TR218A
11.2-28	TR218A
13.6/14.9-28	TR218A
16.9/14.9-28	TR220
16.9-28	

BAN DALAM TRAKTOR	
SIZE	VALVE
16.9-28	TR220
16.9-30	TR218A
18.4-30	TR218A
23.1-30	TR218A
12.4/11-32	TR218A
18.4-34	TR218A
12.4/11.2-36	TR218A
13.6/12-38	TR218A
16.9/18.4-38	TR218A
20.8-38	TR218A

BAN DALAM OTR	
SIZE	VALVE
14.00-25	TR179
15.5-25	TRJ1175C
16.00-25	TR179
17.5-25	TR179
17.5-25	TRJ1175C
18.00-25	TR179
20.5-25	TR179
20.5-25	TRJ1175C
23.5-25	TR179
23.5-25	TRJ1175C
26.5-25	TRJ1175C

TR75A TR78A TR179A	TR13 TR15	TRJ1175C	TR218A TR220
			

Factory Korea : HUNG-A CO., LTD

77, Eosil-ro, Yangsan-si Gyeongsangnam-do, Korea

Factiry Indonesia : PT. HA TIRE

Kawasan HYUNDAI INTERNATIONAL INDUSTRIAL ESTATE Jl. Inti Raya Blok C-5 No.5 Bekasi, Cikarang

www.hunga.com/eng



**AGRICULTURAL
TIRE**

Original Equipment





501 A *R1W											
PAT	DESCPRITION						LUG (ea)	 MAX. LOAD		 INFLATION	
	SIZE	PLY	TYPE	O.D.(mm)	O.W.(mm)	S.D.(mm)		Kg	Lbs	kg/cm2	psi
501A	6.00-12	4	T/T	632	158	26.0	13	325	716	1.80	26

620 *R1											
PAT	DESCPRITION						LUG (ea)	 MAX. LOAD		 INFLATION	
	SIZE	PLY	TYPE	O.D.(mm)	O.W.(mm)	S.D.(mm)		Kg	Lbs	kg/cm2	psi
620	9.5-24	8	T/T	1048	241	30.0	20	1130	2490	3.00	43
	12.4-24	8	T/T	1160	320	33.0	18	1445	3185	2.20	32
	13.6-24	8	T/T	1200	345	34.5	18	1615	3560	2.20	32
	14.9-24	8	T/T	1255	378	34.5	18	1750	3860	1.80	26
	13.6-28	8	T/T	1310	335	35.0	19	1645	3625	2.00	28
	14.9-28	8	T/T	1365	385	35.0	19	1865	4110	1.80	26
	18.4-30	8	T/T	1550	480	38.0	20	2510	5535	1.60	23
	18.4-34	10	T/T	1650	480	38.0	20	2775	6120	1.60	23
	18.4-38	8	T/T	1750	480	38.0	21	2715	5985	1.40	20

603 *R1W											
PAT	DESCPRITION						LUG (ea)	 MAX. LOAD		 INFLATION	
	SIZE	PLY	TYPE	O.D.(mm)	O.W.(mm)	S.D.(mm)		Kg	Lbs	kg/cm2	psi
603	8.3-20	6	T/T	890	202	43.0	15	710	1565	2.40	34
	9.5-24	6	T/T	1056	224	42.5	16	940	2072	2.20	32
	12.4-24	6	T/T	1156	315	48.5	16	1200	2646	1.60	23
	13.6-24	6	T/T	1220	345	54.0	16	1340	2954	1.60	23
	13.6-26	6	T/T	1270	341	54.0	15	1400	3086	1.60	23
	12.4-28	6	T/T	1248	317	48.5	17	1275	2811	1.60	23
	13.6-28	6	T/T	1320	350	52.4	16	1430	3153	1.60	23
	14.9-28	6	T/T	1378	385	54.8	16	1610	3549	1.40	20

617 *R1W											
PAT	DESCPRITION						LUG (ea)	 MAX. LOAD		 INFLATION	
	SIZE	PLY	TYPE	O.D.(mm)	O.W.(mm)	S.D.(mm)		Kg	Lbs	kg/cm2	psi
617	7-14	6	T/T	690	173	26.0	14	440	970	2.40	34
	8-16	6	T/T	789	198	29.0	13	600	1323	2.40	34
	8-18	8	T/T	839	195	32.0	14	780	1720	3.20	46
	11.2-20	8	T/T	1005	297	48.0	14	1120	2469	2.40	34
	12.4-24	6	T/T	1175	308	50.0	16	1445	3186	2.20	32
	14.9-24	8	T/T	1265	378	50.0	15	1750	3858	1.80	26
	13.6-26	6	T/T	1260	345	55.0	15	1580	3483	2.00	28

Made in Indonesia, by PT. HA TIRE
KUALITAS DAN POLA TELAPAK COCOK UNTUK DI INDONESIA - TEKNOLOGI KOREA

HS900 *R1W											
PAT	DESCPRITION						LUG (ea)	 MAX. LOAD		 INFLATION	
	SIZE	PLY	TYPE	O.D.(mm)	O.W.(mm)	S.D.(mm)		Kg	Lbs	kg/cm2	psi
HS900	8-16	6	T/T	789	201	29.0	13	600	1323	2.40	34