



2024 TIRE CATALOG

KOREA Technology Since 1951
INDONESIA Global Factory



TIRON



RIB TYPE

HS317

SIZE	PR	CONST'	RIM	O.D.	O.W.	TREAD DEPTH	MAX. LOAD		INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-15	12	-	6,00	788	215	12,0	Single	1400	87	
							Dual	1320	87	
7.00-16	14	-	5,50	782	199	10,8	Single	1400	105	
							Dual	1335	105	
7.50-16	14	LM	6,00	817	215	12,0	Single	1510	94	 
							Dual	1440	94	
7.50-16	14	SHD	6,00	817	215	12,0	Single	1510	94	 
							Dual	1440	94	

HS308

SIZE	PR	CONST'	RIM	O.D.	O.W.	TREAD DEPTH	MAX. LOAD		INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-16	14	LM	6,00	817	215	12,0	Single	1510	94	 
							Dual	1440	94	
7.50-16	14	SHD	6,00	817	215	12,0	Single	1510	94	 
							Dual	1440	94	

HF1

SIZE	PR	CONST'	RIM	O.D.	O.W.	TREAD DEPTH	MAX. LOAD		INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-16	14	RE	6,00	808	215	10,8	Single	1510	94	
							Dual	1440	94	
8.25-16	14	SHD	6,50	855	230	11,8	Single	1710	83	 
							Dual	1630	83	

HF5


SIZE	PR	CONST'	RIM	O.D.	O.W.	TREAD DEPTH	MAX. LOAD		INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
9.00-20	16	-	7,00	1022	262	12,5	Single	2720	120	
							Dual	2390	110	



Hs315

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
10.00-20	16	LM	7,50	1076	285	16,5	Single	3000	115	
							Dual	2800	105	

Hs500

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
10.00-20	16	LM	7,50	1076	285	16,5	Single	3000	115	
							Dual	2800	105	
11.00-20	16	LM	8,00	1090	290	17,5	Single	3350	115	
							Dual	2900	105	
10.00-20	16	SHD	7,50	1076	285	16,5	Single	3000	115	
							Dual	2800	105	
11.00-20	16	SHD	8,00	1090	290	17,5	Single	3350	115	
							Dual	2900	105	

Hs311

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
10.00-20	16	SHD	7,50	1076	285	17,5	Single	3000	115	
							Dual	2800	105	
11.00-20	16	SHD	8,00	1095	295	18,5	Single	3350	115	
							Dual	2900	105	

Hs366

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
12.00-20	18	-	8,50	1132	325	16,5	Single	3750	115	
							Dual	3550	105	

* SHD = Super Heavy Duty * LM = Long Mileage



LUG TYPE

HS307

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.00-16	14	-	5,50	700	202	16,5	Single	1400	105	
							Dual	1335	105	
7.50-16	14	LM	6,00	812	215	17,5	Single	1510	94	
							Dual	1440	94	
7.50-16	14	SHD	6,00	812	215	17,5	Single	1510	94	
							Dual	1440	94	

HS600

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-16	14	Ultra Grip	6,00	824	215	17,5	Single	1510	94	
							Dual	1440	94	

HS314

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-16	14	SHD	6,00	820	215	17,5	Single	1510	94	
							Dual	1440	94	
8.25-16	14	SHD	6,50	860	228	19,0	Single	1710	83	
							Dual	1630	83	
10.00-20	16	SHD	7,50	1080	285	22,0	Single	3000	115	
							Dual	2800	105	
11.00-20	16	LM	8,00	1100	295	23,5	Single	3350	115	
							Dual	2900	105	
11.00-20	16	SHD	8,00	1100	295	23,5	Single	3350	115	
							Dual	2900	105	

* SHD = Super Heavy Duty * LM = Long Mileage



HT5

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.00-16	14	-	5,50	779	199	12,5	Single	1400	105	
							Dual	1335	105	
9.00-20	16	-	7,00	1024	262	17,5	Single	2720	120	
							Dual	2390	110	

431

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
10.00-20	16	ML	7,50	1080	285	29,0	Single	3000	115	 
							Dual	-	-	
11.00-20	18	ML	8,00	1105	295	30,0	Single	3550	125	 
							Dual	-	-	

HS700

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
11.00-20	18	V-LUG	8,00	1105	295	23,0	Single	3550	125	 
							Dual	3075	115	
11.00-20	18	PRIME	8,00	1105	295	23,0	Single	3550	125	 
							Dual	3075	115	

HS389

SIZE	PR	CONST'	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
12.00-20	18	-	8,50	1130	320	21,0	Single	3724	115	
							Dual	3266	105	

* PRIME = Premium Model * ML = Mining & Logging



Hs309

Hs320

RIB - LUG TYPE

Hs309

SIZE	PR	CONST*	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	 Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-16	14	LM	6,00	820	215	17,5	Single	1510	94	
							Dual	1440	94	
7.50-16	14	SHD	6,00	820	215	17,5	Single	1510	94	
							Dual	1440	94	
10.00-20	16	LM	7,50	1080	285	20,5	Single	3000	115	 
							Dual	2800	105	

Hs320

SIZE	PR	CONST*	 RIM	 O.D.	 O.W.	 TREAD DEPTH	 MAX. LOAD		 INFLATION	 Tire Application
			inch	mm	mm	mm	usage	kg	psi	
7.50-16	14	SHD	6,00	835	215	17,5	Single	1510	94	
							Dual	1440	94	
8.25-16	14	SHD	6,50	860	225	17,0	Single	1750	83	
							Dual	1650	83	
10.00-20	16	SHD	7,50	1080	285	20,5	Single	3000	115	 
							Dual	2800	105	
10.00-20	16	PRIME	7,50	1080	285	20,5	Single	3000	115	 
							Dual	2800	105	
11.00-20	16	SHD	8,00	1095	295	21,5	Single	3350	115	 
							Dual	2900	105	
11.00-20	16	PRIME	8,00	1095	295	21,5	Single	3350	115	 
							Dual	2900	105	

FORKLIFT

HS800

HS800 PNEUMATIC

SIZE	PR	CONST'	RIM	O.D.	O.W.	TREAD DEPTH	MAX. LOAD		INFLATION	Tire Application
			inch	mm	mm	mm	usage	kg	psi	
6.00-9	10	IND	4,00	545	168	14,0	Single	1515	125	
6.50-10	10	IND	5,00	595	185	14,5	Single	1725	115	
7.00-12	12	IND	5,00	685	195	17,0	Single	2445	125	 
8.25-15	14	IND	6,50	848	235	18,5	Single	3830	120	
							Dual	3235	120	
28X9-15	12	IND	7,00	725	220	17,5	Single	2910	98	

TUBE & FLAP

TUBE FORKLIFT

SIZE	VALVE	REGULAR
6.00-9	JS 2	○
6.50-10	JS 2	○
7.00-12	TR 75	○
8.25-15	TR 77	○

TUBE				FLAP
SIZE	VALVE	TYPE		SIZE
		REGULAR	HD	
7.00-15	TR 75 A	○		7.00/7.50-15
7.00-16	TR 177 A	○		7.00/7.50-16
7.50-16	TR 177 A	○	○	7.50/8.25-16
8.25-16	TR 177 A	○	○	8.25/9.00-20
8.25-20	TR 177 A	○	○	10.00/11.00-20
9.00-20	TR 78	○	○	11.00/12.00-20
10.00-20	TR 78	○	○	12.00-24
11.00-20	TR 78	○	○	
12.00-20	TR 78	○	○	
12.00-24	TR 78	○	○	





FACTORY / MARKETING

PT. HA TIRE

Hyundai International Industrial Estate
Jl. Inti Raya Block C-5 No. 5
Cikarang, Bekasi, Indonesia, 17550

CUSTOMER SERVICE

Tel. : 021- 8990 9270 / 2928 8305

 0813-8177-0206

 tiron.co.id

 [tirontire](https://www.facebook.com/tirontire)

 [tirontire](https://www.instagram.com/tirontire)